



Floor Ceiling **60 HZ / A Series** *Standard Efficiency*



R-410A
REFRIGERANT

Standard Efficiency

Flexible installation

Digital display

Washable filter

3D airflow

Floor ceiling Model			CF410A-P024-M3G1C	CF410A-P036-M3G1C	CF410A-P048-M3G1C	CF410A-P060-M3G1C
Power supply		V / Ph / Hz	220V / 1Ph / 60Hz			
Voltage operating range		Min / max volts	198 - 242			
MCA		A	2.30	2.30	2.30	2.30
MOP		A	3.00	3.00	3.00	3.00
Indoor coil	Number of rows / circuits		3 / 4	3 / 4	3 / 5	3 / 5
	Fin spacing / fin type		1.4 mm / Hydrophilic			
	Tube outside diameter / type		Φ7 mm / inner grooved copper tube			
	Coil length x height x width	mm	680×252×40.11	948×252×40.11	1318×252×40.11	1318×252×40.11
Air flow(High speed)		m ³ /h	1200	1800	2100	2100
		CFM	706	1060	1236	1236
Indoor sound level		dB(A)	48-52	51-57	55	55
Dimensions	Dimension (W*H*D)	(mm)	1050×235×675	1250×235×675	1670×235×675	1670×235×675
	Packing (W*H*D)	(mm)	1130×325×765	1380×325×765	1750×325×770	1750×325×770
Weight	Net / Gross	(Kg)	26.5/31	32/37	40/46	40/46
Indoor fan motor	Model		YSK110-59LD-4P17	YSK110-180LD-4P2	YSK110-59LD-4P17	YSK110-59LD-4P17
	Input	W	135	360	160*2	160*2
	Output	W	70	180	85*2	85*2
	Capacitor	uF	3	5	3*2	3*2
	Speed(hi/mi/lo)	RPM	1310/1139/1060	1330/1230/1130	1310/1139/1060	1310/1139/1060
Refrigerant piping	Liquid / Vapor	mm	Φ9.52/Φ15.88	Φ9.52/Φ19.05	Φ9.52/Φ19.05	Φ9.52/Φ19.05
Operation temp		℃	16-32			
Standard Control			Remote controller			
Drain connection		mm	Φ25			